



NOTE:

1. Design and Manufacture for valve according to ASME B16.34.
2. Inspection and Test for valve according to API 598.
3. Connection Screw for valve according to ANSI B1.20.1, ISO 7-1, ISO 228-1, DIN 259/2999.

SIZE	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
d	12	15	18	25	32	40	49	65
L	71.5	83.5	90	116	133	146	200	237
H	33.5	41.5	52	58	66.5	78	96.5	112.5
h	9	11	12	12	15	15	18	18
KXK	9X9	9X9	9X9	11X11	14X14	14X14	17X17	17X17
A	36	36	42	42	50	50	70	70
B	42	42	50	50	70	70	102	102
a	3	3	3	3	3.5	3.5	4.5	4.5
b	3	3	3.5	3.5	4.5	4.5	5.5	5.5

14	Q15F-1000-12	CROWN WASHER	1	304
13	GB/T 6172.1-2000	NUT	1	A194-8
12	Q15F-1000-11	DISH SHRAPNEL	2	304
11	Q15F-1000-10	GLAND	1	304
10	Q15F-1000-09	WEAR WASHER	1	PTFE+25% GF
9	Q15F-1000-08	PACKING	1	PTFE
8	GB/T 3452.1-2005	O RING	1	FPM
7	Q15F-1000-07	STEM WASHER	1	PTFE+25% GF
6	Q15F-1000-06	STEM	1	CF8/CF8M
5	Q15F-1000-05	GASKET	3	PTFE
4	Q15F-1000-04	BONNET	1	CF8/CF8M
3	Q15F-1000-03	BALL	1	304/316
2	Q15F-1000-02	SEAT	4	PTFE
1	Q15F-1000-01	BODY	1	CF8/CF8M
NO.	DRAWING NO.	DESCRIPTION	Q' TY	MATERIAL

ZHEJIANG MINTN VALVE CO., LTD.

Describe	Ball valve
Model	Q15F-16P
Web	www.mintn.com
TEL	+86-577-55558668